

March 17, 2022

Hayride Attraction Application Checklist

(all references refer to ASTM F3168)

1. The tow vehicle (tractor) is adequately sized to control a fully loaded wagon or trailer. (Section 5.3) _____ INITIALS

The tow vehicle shall have the weight, capacity and traction to be able to control a fully loaded wagon/trailer. All tow vehicles or the wagon/trailer shall be equipped with a fire extinguisher.

2. An operator's manual for the hayride attraction are specific to your operation, in writing, is included. (Section 6.4.1). _____ INITIALS
3. Owner/operator has an inspection program appropriate for their equipment and venue including specific points of inspection and intervals. Inspection checklists for pre-operation/post (daily) of the tow vehicle, wagon/trailer and trail are included or incorporated in the operator's manual. (Section 6.5.1, 6.5.3.1 & 6.5.4) _____ INITIALS

The tow vehicle shall be thoroughly inspected prior to seasonal operations and daily thereafter on operational days. Specific items that shall be inspected include, but are not limited to: Fluid levels, tire pressure, tire wear, lug nuts, brakes, bearings, headlights (if operating in limited visibility or darkness) and towing apparatus.

4. All tow vehicle (tractor) drivers are properly trained with documentation of training maintained on site (Section 6.7.2.) _____ INITIALS
5. Maintenance record for all tow vehicles (tractors) and wagons or trailers is available on site. (Section 6.5.3) _____ INITIALS
6. The maximum operating speed is clearly posted on the tow vehicle (tractor) and adhered to. (Section 6.8) _____ INITIALS
7. Tow vehicles (tractors) have operating signal lights and required edge markings. (Section 6.9.1) _____ INITIALS
8. There is a communication system between the wagon or trailer attendant and tow vehicle driver. (Section 6.10) _____ INITIALS
9. The tow vehicle's (tractor's) draw bar secures and is adequately sized for the wagon or trailer being used. (Section 6.5) _____ INITIALS

10. The wagon or trailer has a tamper-proof locking hitch connecting the wagon or trailer to the tow vehicle (tractor). (Section 5.4.2) _____ INITIALS

11. A safety chain or steel cable of appropriate strength is installed to connect the wagon or trailer to the tow vehicle (tractor). The safety chain or cable is attached with a locking device that cannot accidentally become detached. (Section 5.4.3) _____ INITIALS

12. The loading and unloading zone are clearly marked, level; has safety fencing, lighting and signage as necessary. (Section 6.9.1) _____ INITIALS

13. The wagon or trailer has a patron barrier or bulkhead installed along the side of the wagon or trailer closest to the tow vehicle that will prevent anyone from exiting the wagon or trailer on the side closest to the tow vehicle? (Section 5.4.1) _____ INITIALS

14. Trailer or wagon is marked with a unique identifiable feature so that it can easily be identified. Examples are numbers, letters, symbols, colors, etc. (Section 5.5) _____ INITIALS

15. Is or has a qualified inspector who is certified to perform pre-operation, post operation (daily) inspections. _____ INITIALS

Name

Signature

Date

Business Name

Address

Telephone Number

E-mail